

COMPANY PROFILE JTC LIGHTING

THE FUTURE OF ADVANCE LIGHTING



We are Dealers, Distributors and top suppliers of major brands in LED Lighting and lighting fixtures as well, we are also dealing & manufacturing in our own Brands JTC Lighting. We have vast range of LED Lighting products. We promise to help you lighten & brighten your homes or workplaces with a motive of achieving lighting cost across the Pakistan. JTC Lighting working hard to earn the customer's satisfaction, trust and respect to provide best quality and services with affordable cost effective prices from the market.

VISION

To be a recognized as the best leading provider of value, services and quality in project of lighting

MISSION

To provide our clients competitive and premium quality with services of our all products JTC Lighting aims to become the most trusted LED lighting suppliers in Pakistan.



These LED Bulb are recognized as a solution for the most commercial, industrial, retail and special applications. JTC LED Bulbs are designed to reduce lighting costs without compromise to the visual quality of indoor lighting environments.

FEATURES

- · Constant Flow Quick Start
- · Low Heat Dissipation Design
- High Shock /Vibration resistant
- · Internal constant current driver
- · Surge Protection for Voltage Fluctuation
- · Double E core transformer
- · Easy to install, Dust Proof
- · Prevent Electricity Leakage
- · Mercury free and don't emit UV
- · 3X More Aluminum for Heat Dissipation

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|--------|------------------|----------------------|-----------------|--------------|---------|
| 7 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 12 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 13 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 18 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 30 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 50 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 70 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| WARRANTY | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year |



LED SMD DOWNLIGHT

With more than 30,000 hrs lifespan, easy to install and low-cost maintenance design, JTC Lighting introduces the new standard range of LED Platinum Downlightes that transforms ambient lighting into an exquisite balance of refined appearance with

FEATURES

- Constant flow, Quick start
- 30000 hours Lifespan
- · Easy to install, dustproof

- · Prevents electricity leakage
- · Energy Efficient
- Best build quality

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|-----|------------------|----------------------|-----------------|--------------|---------|
| 5 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 7 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 12 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 18 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |



without compromise to the visual quality of indoor lighting environments. The downlights saturates your interior space with a strong and uniformed glow. Its sophisticated recessed design is perfect as a new downlight installation or a lighting

FEATURES

- · External constant current driver
- · Constant flow, Quickstart
- · 50000 hours Lifespan
- · Complete aluminum body design
- · Driver outside fixture
- · Hight Shock / Vibration resistant
- · Easy to install, dustproof
- · Prevents electricity leakage

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|-----|------------------|----------------------|-----------------|--------------|-------------|
| 5 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 7 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 12 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 100 lmw |
| 18 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 110-130 lmw |
| 20 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 110-130 lmw |



JTC LED track light series are powered by imported high power, high performance chips with fashinable appearance. Thus they can meet customers lighting demands. It improves the lighting environment, save more energy and be greener and more economical in the precondition of same lighting effect.

FEATURES

- · Shopping malls
- · Clothing brands outlets
- · Cozy living room

- · Shoes outlets
- · Beauty parlor outlets
- Dark hallway

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|-----|------------------|----------------------|-----------------|--------------|-------------|
| 20 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130-145 lmw |
| 25 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130-145 lmw |
| 30 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130-145 lmw |
| 40 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130-145 lmw |



JTC LED Panel Light transforms ambient lighting into an exquisite balance of refined appearance and superior efficiency. When illuminated, the panels deliver exceptional uniform light, to all over the area, its flicker free technology provides super dynamic balanced light resulting a modern look and economic lighting sourse. It saves energy up to 80% with an incredible lifespan of more than 3 to 5 years.

FEATURES

- · Energy-saving about 80%Efficient
- · Long-life span more than 5 years
- · 50000 hours life span

- · Soft and wide light emittance
- · No ultraviolet or infrared rays
- · Isolated power supply without any safety problem

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|-----|------------------|----------------------|-----------------|--------------|---------|
| 12Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 18 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 32 Watts | 90-265 | >85 | 30,000 hrs | 3000k,4000k,6500k | 0.67 | IP 44 | 100 lmw |
| 36 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |
| 40Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |
| 48 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |



JTC LED Panel are a type of lighting fixture designed to replace conventional fluorescent celling lights. They are one of best lighting options for indoor settings. This LED technology has been widely used for quite some time now, but panel lights that use the technology are fairly new to the market, and are gaining ground due to the sleek look, and innovative features and design.

FEATURES

- · Energy-saving about 80%Efficient
- · Long-life span more than 5 years
- 50000 hours life span
- **SPECS**

- · Soft and wide light emittance
- No ultraviolet or infrared rays
- Isolated power supply without any safety problem

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|-----|------------------|----------------------|-----------------|--------------|---------|
| 36Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |
| 40 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |
| 48 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |
| 60Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 44 | 130 lmw |



JTC Flood Light is an extremely flexible and versatile LED solution that ensure an excellent quality of light, targeted where is required, at the same time allows to decrease the hot spot and improve the light distribution onto the higher position for building facade.

FEATURES

- · provides even and bright illumination
- Aluminum alloy shell for better heat dissipation
- · 50000 hrs lifespan
- · Ingress Protection Grade IP65 · Ultra energy efficient up to 80%

SPECS

POWFR INPUT CRI I FD I IFF COLOR POWFR LUMENS IP VOLTAGE SPAN **TEMPERATURE FACTOR** RAting 50 Watts 90-265 >85 50,000 hrs 3000k.4000k.6500k IP 66 120-145 lmw 0.95 100 Watts 90-265 IP 66 >85 50,000 hrs 3000k,4000k,6500k 0.95 120-145 lmw 150 Watts 90-265 >85 50,000 hrs 3000k,4000k,6500k IP 66 120-145 lmw 0.95 200 Watts 90-265 >85 50,000 hrs 3000k.4000k.6500k IP 66 0.95 120-145 lmw



JTC LED Hight Bay Lights/Low Bay Lights are specifically designed for taller ceilings and larger areas. They focus light more directly to create powerful illumination at a long range, making them perfect for commercial and industrial applications such as warehouses and retail stores.

FEATURES

- Easy Installation, Protected from dust, powder-coated paint resistant to corrosive and salty environments
- Available in Aluminum Doom and in different sizes.
- Extra Grip on Light by its installation strip
- Aluminum to withstand the high-tempera ture rise and round the clock operations • Ventilation system designed on back doom

· Its magnificent Doom is made of

 Ventilation system designed on back doom to extend the life of LED lens to improve the visuals of the product

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RATING | LUMENS |
|-----------|------------------|-----|------------------|----------------------|-----------------|--------------|-------------|
| 50Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 120-145 lmw |
| 100 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 120-145 lmw |
| 150 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 120-145 lmw |
| 200 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 120 lmw |



LED HIGHWAY/STREET LIGHT

JTC LED Highway lights are built with premium quality material that is aluminum body for better heat dissipation results in better lifespan of the LED light source. It is IP 65 grade which means it is protected against dust and water which makes it suitable for outdoor use. It is very energy efficient that can save up to 80% energy comparing to traditional lighting fixtures.

FEATURES

- All aluminum housing for better heat dissipating, extending the life span of lense lighting source
- · Protection Grade IP 65

- Free of dust and water, suitable for outdoor installations
- Save 80% more energy compared to the traditional lighting fixtures

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|-----------|------------------|-----|------------------|----------------------|-----------------|--------------|---------|
| 60Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 130 lmw |
| 100 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 130 lmw |
| 150 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 130 lmw |
| 200 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 65 | 130 lmw |



JTC LED T8 tube rods strip Light and batten light/vanity light add an extensive array of lights of any environment at the flick of a switch with JTC LED T8 tube rods strip Light and batten light/vanity light. With easy installation, minimal space requirement and 50000 hours life span LED strip light is made by special different view angles mixing lighting design with excellent heat dissipation, making it the perfect choice for your ambiance.

FEATURES

- · Excellent replacement for old T8 fluorescent Lights
- · Designed to manage heat dissipation
- · Conventional lighting fixture with modern era design
- · 50000 hours Lifespan
- · Light to light connecting facility
- · High efficiency constant current
- driver
- · Brighter with less degradation than T8 fluorescent lights

| POWER | INPUT VOLTAGE | CRI | LED LIFE SPAN | COLOR TEMPERATURE | POWER FACTOR | IP RAting | LUMENS |
|----------|------------------|-----|------------------|----------------------|-----------------|--------------|-------------|
| g Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.67 | IP 54 | 115-135 lmw |
| 18 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 54 | 115-135 lmw |
| 40 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 54 | 115-135 lmw |
| 60 Watts | 90-265 | >85 | 50,000 hrs | 3000k,4000k,6500k | 0.95 | IP 54 | 115-135 lmw |

OUR SERVICES

JTC Lighting is providing its quick services & dealing in various following sectors:

- Commercial
- Domestic
- Residential
- Institutional

- Industrial
- · Indoor Lights
- · Outdoor Lights

OUR VALUED CUSTOMERS

















































www.jtctrading.com lites.jtc@gmail.com info@jtctrading.com

Main Market Muslim Town Lahore Pakistan